

Road Strategy Procedures

Service Levels	1	2	3	4	5	6		
Design Speed KPH	100	Urban 50	Rural 100	Urban 50	Rural 100	Urban 50	Rural 60	NA
Surface	Sealed	Sealed	Sealed	Sealed/Gravel				NA
Travel lanes	2 Lane	2 Lane	2 lane	2	2		1	NA
Lane Width (Metres)	3.5	3	3	3	3		4	NA
1m Sealed Shoulder	yes	yes	no	no	no		no	NA
500mm Sealed Shoulder	yes	yes	yes	no	no		no	NA
1m Gravel Shoulder	yes	no	yes	yes	yes		yes	NA
Line Marking	yes	no	over crests	over crest				NA
Guideposts	yes spaced 150m	no	yes spaced 250m	no	yes spaced 250m	only at culverts & curves	only at dangerous locations	NA
Roughness Counts/intervention	4		5		4-6	6-8	8-11	NA
Signs-Crests	yes	NA	yes	NA	yes	yes	no	NA
Signs-Curves	yes	NA	yes	NA	yes	yes	no	NA
Signs-Speed Advisory	yes	NA	yes	NA	yes	yes	no	NA
Vegetation Shoulder	6m	NA	4m	NA	4m	4m	2m	NA
Vegetation Clearance-Heights	5.5m	NA	4.6m	NA	4.6	4.6	4.6m	NA
Shoulder Annually	yes	NA	yes	NA	yes	yes	yes	NA
Roadside Slashing	if required	NA	if required	NA	if required	if required	no	NA
Pothole Patching	Response	1 week	1 week		1 month	3 months	12 months	NA
Guideposts	Defect- Response	1 month	3months		3 months	6months	6 months	NA
Warning Response Time	Sign Defect	24 hours	1 week		1 week	2 weeks	2 weeks	NA
Vegetation Time	Defect-Response	1 month	3 months		6 months	9 months	12 months	NA